

# U-CHANNEL, V-GROOVE & SEAMLESS CLADDING AND SOFFIT



## TESTING

- CCMC 14323-R
- ICCES-ESR 4560
- CAN/ULC-S134
- NFPA285
- NFPA268
- CAN/ULC-S745-11
- ASTM D3679-17
- ASTM D696-16
- ASTM D635-18
- CAN/CGSB – 41.24-95
- CAN/ULC S102-2018
- ASTM G154-16
- ASTM D790
- ASTM G155
- ASTM E330/E330-14  
PROCEDURE B Q50<0.85
- ASTM C518-17 (MODIFIED)
- RILEM TC -127-MS  
ACID RAIN

## FINISHES

WOODGRAINS, SOLID COLORS, BRUSHED FINISHES,  
INTERIOR FINISHES  
NON-STOCK COLORS AVAILABLE (ADDITIONAL LEAD TIMES)

## EXTERIOR WALL PANEL

6" - 12' & 20'  
12" - 12' & 20'  
CUSTOM LENGTHS AVAILABLE

## LEAD TIMES

2-3 WEEKS FOR STOCK COLORS + SHIPPING  
3-6 WEEKS FOR NON-STOCK COLORS + SHIPPING  
(OUTSIDE OF WESTERN CANADA)

## PVC TRIMS

J-TRIM, 2PC FINISH TRIM,  
2PC TERMINATION WALL TRIM,  
OUTSIDE CORNER, INSIDE CORNER  
H-MOULD, F TRIM, STARTER STRIP

## CHAMCLAD ADVANTAGE

- 50 YEAR WARRANTY
- LEED COMPLIANT
- CLASS A FIRE RATED
- SCRATCH & GRAFFITI RESISTANT
- SUPERIOR UV PROTECTION
- IMPERVIOUS TO WATER ABSORPTION, BACTERIA AND MOLD
- LOW MAINTENANCE
- HIGH IMPACT RESISTANCE
- SHORT LEAD TIMES
- NORTH AMERICAN MANUFACTURED FROM 100% RECYCLED RIGID PVC
- CANADA AND US DISTRIBUTION

## PVC/ALUMINUM TRIMS

OUTSIDE CORNER, FINISH TRIM,  
STARTER STRIP

