

4" & 6" SOFFIT ENGINEERED RECYCLED RIGID PVC



TESTING

- CLASS A FIRE RATED
- ICCES-ESR 4560
- ASTM D3679-17
- ASTM D635-18
- ASTM E119-22
- ASTM G154-16
- ASTM G155-21
- TAS 202 & 203 (MIAMI TESTING STANDARDS)
- AAMA 303-19
- AAMA 307-16
- AAMA 664-21

CHAMCLAD 1/2" WALL PANELS MAY BE USED FOR SOFFIT APPLICATIONS – Venting supplied by others.

3/8" SOFFIT PANELS

4" - 12' & 20'

6" - 12', 16', 20' & 30'

CUSTOM LENGTHS AVAILABLE

VENTED PANELS

4" - 12' & 20'

6" - 12', 16' & 20'

ALUM/ PVC TRIMS

1PC UNIVERSAL J-TRIM, 2PC J-TRIM (2" & 3.5"), 2PC OUTSIDE CORNER (2" & 3.5"), 2PC H-TRIM (2" & 2.75")

LEAD TIMES

1-2 WEEKS FOR STOCK COLORS + SHIPPING

2-3 WEEKS FOR NON-STOCK COLORS + SHIPPING

FINISHES

WOODGRAINS, SOLID COLORS, BRUSHED METALLICS, ANODIZED & INTERIOR FINISHES
NON-STOCK COLORS AVAILABLE
(ADDITIONAL LEAD TIMES)

CHAMCLAD ADVANTAGE

- 50 YEAR WARRANTY (15 YEARS NON PRORATED)
- MAY CONTRIBUTE TO LEED CERTIFICATION
- SCRATCH & GRAFFITI RESISTANT
- SUPERIOR UV PROTECTION
- IMPERVIOUS TO WATER ABSORPTION, BACTERIA AND MOLD
- LOW MAINTENANCE
- HIGH IMPACT RESISTANCE
- SHORT LEAD TIMES
- NORTH AMERICAN MANUFACTURED FROM 100% RECYCLED RIGID PVC
- CANADA AND US STOCKING & DISTRIBUTION

