

6" CLASSIC WALL PANEL (U-CHANNEL & V-GROOVE)



TESTING

- CCMC 14323-R
- CAN/CGSB – 41.24-95
- CAN/ ULC S101-14
- CAN/ULC S102-18
- CAN/ULC S102.2-18
- CAN/ULC-S134-13-REV1
- ASTM D3679-17
- ASTM E119-22
- ASTM E330/ E330M-14(2021)
- ASTM G154-16
- ASTM G155-21
- ASTM D635-18
- AAMA 303-19
- AAMA 307-16
- AAMA 664-21

Please note: Our exterior wall panel may also be used in soffit or interior applications. However When using our 1/2" panel for soffit applications venting is supplied by others

1/2" EXTERIOR WALL PANEL
6' - 12', 16', 20' & 30'
CUSTOM LENGTHS AVAILABLE

ALUMINUM /PVC TRIMS
2PC OUTSIDE CORNER (2" & 3.5"),
2PC J-TRIM (2" & 3.5"), 2PC
ALUMINUM H-TRIM (2.75"), 1PC PVC
INSIDE CORNER, STARTER STRIP

LEAD TIMES
1-2 WEEK LEAD TIME FOR STOCK
COLORS + SHIPPING
2-3 WEEKS FOR NON-STOCK COLORS
+ SHIPPING

Finishes
WOODGRAINS, SOLID COLORS, BRUSHED FINISHES,
INTERIOR FINISHES
NON-STOCK COLORS AVAILABLE (ADDITIONAL LEAD
TIMES)

- CHAMCLAD ADVANTAGE**
- 50 YEAR WARRANTY
 - CONTRIBUTES TO LEED CERTIFICATION
 - SCRATCH & GRAFFITI RESISTANT
 - SUPERIOR UV PROTECTION
 - IMPERVIOUS TO WATER ABSORPTION,
BACTERIA AND MOLD
 - LOW MAINTENANCE
 - HIGH IMPACT RESISTANCE
 - SHORT LEAD TIMES
 - CANADIAN MANUFACTURED
FROM 100% RECYCLED RIGID PVC

